

YUEQING QUNLI ELECTRIC

PG Type Plastic Waterproof Nylon Cable Gland

Material:

Adopting nylon PA66 certificated by UL

Weather strip:

Nitrile butadiene rubber (NBR),
Weatheringresistance
rubber (EPDM)

Working temperature:

-40°C to 100°C in static state, instantaneous heat
resistance up to 120°C; -20°C to 80°C in dynamic
state, instantaneous heat resistance up to 100°C

Characteristics:

IP68(Rotate the part, and use O ring)

Color:

Black(RAL9005), light grey(RAL7035), as
well as special colors that can be designed at
request.



Type	CableRange (mm)	Thread O.D.AG(mm)	Thread Length GL (mm)	Spanner Size (mm)
PG7	3~6.5	12.5	8	16
PG7	2~5	12.5	8	16
PG9	4~8	15.2	8	19
PG9	2~6	15.2	8	19
PG11	5~10	18.6	8	22
PG11	3~7	18.6	8	22
PG13.5	6~12	20.4	10	24
PG13.5	5~9	20.4	10	24
PG16	10~14	22.5	10	27
PG16	7~12	22.5	10	27
PG19	12~16	24	10	27
PG19	10~13	24	10	27
PG21	13~18	28.3	10	33
PG21	9~16	28.3	10	33
PG25	16~21	30	11	35
PG25	13~18	30	11	35
PG29	18~25	37	12	42
PG29	13~20	37	12	42
PG36	22~32	47	14	52
PG36	20~26	47	14	52
PG42	32~38	54	14	60
PG42	25~31	54	14	60
PG48	37~44	59.3	15	64
PG48	29~35	59.3	15	64
PG63	42~50	71	28	77
PG63	32~40	71	28	77